

# **Camtainer® Insulated Containers**

For Hot and Cold Beverages

Models 100LCD 1<sup>1</sup>/<sub>2</sub> gallon (5,5 L) 250LCD 2<sup>1</sup>/<sub>2</sub> gallon (9,4 L)

For Soup (No Spigot)

Model 350LCD 3<sup>3</sup>/<sub>8</sub> gallon (12,7 L)



#### **Features & Benefits**

- Attractive design is perfect for front-of the-house hot and cold beverage or soup service. Stacks easily for storage and transportation.
- · Serving capacity:

Model 100LCD - 27 each 7 oz. (210 mL) cups Model 250LCD - 45 each 7 oz. (210 mL) cups Model 350LCD - 61 each 7 oz. (210 mL) servings

- Single-molded, seamless, double-wall, high-density, polyethylene construction is highly durable, dishwasher safe and resists dings and dents. Textured exterior is scratch-resistant.
- Polyurethane foam insulation provides excellent hot or cold temperature retention for hours. Hot beverages remain hot without the need for a costly external heating source.
- Molded-in handles offer comfortable easy transporting.
- Recessed sturdy plastic latches will not rust or corrode and are protected from being hit or damaged.
- Drip proof recessed spigot (on 100LCD & 250LCD) allows for convenient access. Optional Easy Serve Dispenser lever attaches easily and offers easy and even beverage dispensing.
- Raised edge, spill proof rim prevents spills and leaks during transport.
- Pop-up vent on all models helps to equalize pressure and release steam.
- Self-adhesive beverage labels included for quick identification of contents.
- Optional Condiment Holder and Riser available for 250LCD.
- Optional Camdollies® offer easy transporting.
- Non-electrical.
- · No assembly required.
- · Available in 8 colors.

Ite	m	Λ	n
11.5	<b>5      </b>		v.

Specifier Identification No.

Model No.

Quantity\_\_\_\_\_





Easy Serve Dispenser



Spill Proof Rim and Molded-in Handle.

HUI				
200°F (93°C)	192°F (89°C)	190°F (88°C)	187°F (86°C)	185°F (85°C)
Starting Temperature	1 hr.	2 hrs.	3 hrs.	4 hrs.








### **Camtainer® Insulated Containers**

For Hot and Cold Beverages

Models 100LCD 1<sup>1</sup>/<sub>2</sub> gallon (5,5 L) 250LCD 2<sup>1</sup>/<sub>2</sub> gallon (9,4 L)

For Soup (No Spigot)

Model 350LCD 33/8 gallon (12,7 L)




(47 cm)

Specifier Identification No.

Model No.

Quantity



Dimension Tolerance: +/- 1/4" (0,64 cm)

### **Specifications**

Code	Description	Total Capacity	Serving Capacity 7 oz. (210 mL) cups	Dimensions W x D x H	Case lbs./cube Kg/m³	
100LCD	Camtainer	1½ gallon (5,5 L)	27	103/8" x 113/4" x 171/4" (26 x 30 x 43 cm)	9.5 (1.24) 4,5 (0,035)	
250LCD	Camtainer	2½ gallon (9,4 L)	45	9" x 165%" x 18½" (23 x 42 x 46 cm)	12.75 (1.70) 6 (0,05)	
350LCD	Camtainer for Soup (No Spigot)	33/8 gallon (12,7 L)	61	9" x 165%" x 183%" (23 x 42 x 47 cm)	13.25 (1.70) 6 (0,05)	

## Optional Accessories

350LCD (No Spigot)

#### **Standard Colors**

 □ Navy Blue (186)
 □ Slate Blue (401)
 □ Coffee Beige (157)

 □ Dark Brown (131)
 □ Brick Red (402)
 □ Green (519)

 □ Black (110)
 □ Hot Red (158)

### **Architect Specs**

The portable, non-electrical hot and cold beverage and soup container/server shall be a Camtainer Insulated Container, Models ...., manufactured by Cambro Mfg. Co., Huntington Beach, CA 92647 U.S.A. It shall be made of one-piece, seamless, double-wall polyethylene and foam-injected polyurethane. It shall have a raised edge, spill-proof rim. It shall have a pop-up vent to help equalize pressure and release steam. It shall have durable, plastic latches on recessed, molded-in mounting plates. It shall have molded-in handles. It shall have a drip proof, recessed serving spigot designed with easy finger adjustment on 1½ gallon (5,5 L) and 2½ gallon (9,4 L) container. It shall have the option of an Easy Serve

Dispenser lever. It shall be available without a spigot for soup service. It shall have self-adhesive beverage labels to use for quick product identification. It shall have an optional Condiment Holder and Riser except for the 100LCD. It shall require no assembly and shall be offered in 8 colors.

### **Approvals**



