Heater Proofers - Non-Insulated Standard Full & 1/2 Height 100% Pre-Tested Electrical Assembly

- Heavy Duty, aluminum construction designed for durability.
- Easy to Clean.
- Forced air design provide even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Front casters are provided with brakes.
- Easy dual proof/heat control:
- "Proof/humidity" mode: Up to 95% humidity at 110°F (43°C)
- "Heat" mode: Maximum Temperatures up to 180°F (82°C)
- Corner bumpers provide protection to unit, associates & fixtures.
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on the inside door frame.
- Door opens 270 degrees. Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- Drip trough catches condensation. Internal water pan collects condensation or is used in proofer mode.
- All controls are accessible without opening cabinet door. Easy to read real time LED thermometer display.
- Pan Capacity: 35 18" x 26" pans NHPL-1836C 10 - 18" x 26" pans NHPL-1810HHC

Electrical specifications:

- 120 Volt–60 Hz, NEMA 5-15P
- 1440 Watts: 14.0 AMPS Plug into any standard 110 outlet.

Model Number	Order#	Overall Dimensions						Approx.	
		Width		Length		Height		Ship Wt	
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1836C	684684	21	533	30¾	781	66½	1,689	136	106
NHPL-1810HHC	684625	21	533	30¾	781	66½	1,689	91	41

Caster Information

Swivel Plate Caster with 5" Polyurethane Wheel 738A (128784)

Swivel Plate Caster with 5" Polyurethane Wheel & Brake 738ABK (204185)

5" Polyurethane Wheel 7112 (122180)











HEATER-PROOFER

NHPL-1836C

NHPL-1810HHC Fits under counters and tables.

For replacement parts please see page 143.

